



**QC STL PRO-2.5X**  
**QuietCool Original Classic Line**

**QC STL PRO-2.5X Specifications**

|  |   |  |
|--|---|--|
| Motor Voltage                                      | 120 VAC, 60 Hz  |  |
| Energy Use   | Hi: 157 Watts / Low: 82.3 Watts   |  |
| Air Flow   | Hi: 2541 CFM / Low: 2018 CFM  |  |
| HVI-916 Airflow (for CA Title 24 New Construction) | 1920 CFM  |  |
| dBA  | Hi: 43.2 / Low: 37.2  |  |
| Recommended SQFT Coverage @ 2 CFM per SQ FT        | Covers 847 SQFT to 1271 SQFT  |  |
| # of Speeds  | 2   |  |
| Duct Diameter                                      | 16"   |  |
| Duct Length  | 6 feet  |  |
| Motor Head Diameter                                | 16 1/2"   |  |
| Motor Head Length                                  | 13 1/2"   |  |
| Dampers  | Barometric Pressurized R5 Dampers   |  |
| Controls (Not Included)                            | Included 8 Hour Electronic Timer and HI-LOW-OFF switch  |  |
| Warranty   | 15 Years  |  |
| Framing  | None Required   |  |
| Joist Cutting                                      | None Required; fits 16" or 24" on center  |  |
| Minimum Suggested Attic Venting                    | 3.39 SQ FT net free area  |  |
| Ceiling Rough Opening                              | 14 1/4" x 18 1/4"   |  |
| Removable Grille Outside Dimension                 | 16" x 20"   |  |
| Shipping Weight                                    | 49 lbs.   |  |
| Box Dimensions                                     | 24" x 20" x 38"   |  |
| In The Box   | <ul style="list-style-type: none"> <li>-QC STL PRO-2.5X Motorhead</li> <li>-Removable Grille</li> <li>-Cut-out Template</li> <li>-Window Locks</li> </ul> | <ul style="list-style-type: none"> <li>-Damper Box</li> <li>-6 Foot Duct</li> <li>-Accessory Bag</li> <li>-Controls</li> </ul> |



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)