QuietCool®
ADVANCED WHOLE HOUSE FANS

QC STL PRO-5.5X Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi: 490 Watts / Med: 268 Watts / Low: 88 Watts
Air Flow	Hi:5044 CFM / Med:4238 CFM / Low:2870 CFM
HVI-916 Airflow (for CA Title 24 New Construction)	3750 CFM
dBA	Hi: 50.7 / Med: 45.7 / Low: 35.6
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers 1681 SQFT to 2522 SQFT
# of Speeds	3
Duct Diameter	20″
Duct Length	9 feet
Motor Head Diameter	20 1/2″
Motor Head Length	13 1/2″
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16″ or 24″ on center
Minimum Suggested Attic Venting	6.73 SQ FT net free area
Ceiling Rough Opening	14 1/4″ x 30 1/4″
Removable Grille Outside Dimension	16″ x 32″
Shipping Weight	97 lbs.
Box Dimensions	39″ x 24″ x 39″
In The Box	-QC STL PRO-5.5X Motorhead -Damper Box -Removable Grille -9 Foot Duct -Cut-out Template -Accessory Bag -Window Locks -Controls

For more information, visit our website at:
QUIETCOOLSYSTEMS.COM