



QC STL PRO-6.0X
QuietCool Stealth Pro Line

QC STL PRO-6.0X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 462 Watts / Med: 210 Watts / Low: 113 Watts	
Air Flow	Hi:5587 CFM / Med:4262 CFM / Low:3428 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	4030 CFM	
dBA	Hi: 51.1 / Med: 45.7 / Low: 38.5	
Recommended SQFT Coverage @ 2 CFM per SQ FT	Covers 1862 SQFT to 2794 SQFT	
# of Speeds	3	
Duct Diameter	22"	
Duct Length	9 feet	
Motor Head Diameter	22 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	7.45 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 36 1/4"	
Removable Grille Outside Dimension	16" x 38"	
Shipping Weight	103 lbs.	
Box Dimensions	41" x 26" x 39"	
In The Box	-QC STL PRO-6.0X Motorhead -Removable Grille -Cut-out Template -Window Locks	-Damper Box -9 Foot Duct Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM